

SmartReader Plus 6

Product Specifications

Type: Eight-Channel Temperature Thermocouple

GENERAL SPECIFICATIONS

Size: 107 mm x 74 mm x 22 mm (4.2" x 2.9" x 0.9")
Weight: 110 grams (3.75 ounces)
Case Material: Noryl® plastic
Battery: 3.6 volt Lithium
Resolution: 12-bit (1 part in 4096)
Mounting: Magnetic backing or locking eyelet
Clock Accuracy: +/- 2 seconds per day
Sampling Methods: Continuous (First-in, First-out)*, Stop When Full (Fill-then-stop)
**Not available with sample rates faster than eight seconds*
Operating Limits: -40 to 70°C (-40 to 158°F) and 0 to 95% RH (non-condensing)
PC Requirements: IBM PC or 100% compatible with at least one free serial port, 2 MB of RAM memory, and 2 MB of hard disk space
Software Requirements: TrendReader® Standard (compatible with Windows® 3.1, '95, '98, 2000, Me, NT and XP)

Memory Size: 32KB (capable of storing up to 21,500 readings)
 (3 models available) 128KB (capable of storing up to 87,000 readings)
 1.5MB (capable of storing up to 1,048,000 readings)
Sampling Rates: User selectable rates from 25 per second to once every eight hours (BP-101 battery pack or PS-201 power supply required for sampling rates faster than eight seconds)
Number of Channels: Eight (one internal thermistor for cold-junction compensation and seven thermocouple inputs)

SENSOR SPECIFICATIONS

Temperature Sensor (internal)


Type: NTC Thermistor - 10,000 Ohm @ 25°C (77°F)
Range: -40 to 70°C (-40 to 158°F)
Accuracy: +/- 0.2°C over the range of 0 to 70°C (+/- 0.3°F over the range of 32 to 158°F)
Resolution: 0.03°C (0.05°F) @ 25°C; better than 0.07°C (0.12°F) between -25 and 70°C (-13°F and 158°F); better than 0.13°C (0.23°F) between -40 and -25°C (-40°F and -13°F)

Thermocouple Wire	Range	Resolution
J type	-50 to 600°C (-55 to 1100°F)	0.30°C (0.55°F)
K type	-100 to 1150°C (-145 to 2100°F)	0.50°C (0.90°F)
S type	0 to 1450°C (32 to 2642°F)	1.0°C (1.8°F)
T type	-200 to 400°C (-325 to 750°F)	0.40°C (0.75°F)
E type	-50 to 680°C (-58 to 1250°F)	0.24°C (0.44°F)

Accuracy

+/- 0.5% of range + resolution

Monitor temperature over a wide range with the SmartReader Plus 6 data logger. Easily and accurately record temperature from any J, K, S, T or E type thermocouple probe. With seven inputs for thermocouple probes and an on-board cold-junction thermistor, the SRP6 is one of the most versatile thermocouple data loggers available.



WARRANTY

Internal Battery: 10 Years
Data Logger: 3 Years

APPLICATIONS

Monitoring performance of gas-fired heating equipment, verifying concrete curing temperatures, process verification, etc.

Model#:	Cat#:
SRP-006	01-0013
SRP-006-128K	01-0122
SRP-006-1.5M	01-0151